UNITED KINGDOM DYNAMIC PLATE TEST DEVICES ACCREDITATION TRIAL SUMMARY TEST CERTIFICATE

Report No: 0127DPT/8002 214 Issue 13

DYNATEST FWD 8002 SERIAL NUMBER: 214 TRL Reference No: 16

Operated by PTS of Britannia House, 1 Rough Hey Road, Grimsargh, Preston

has participated in a United Kingdom DPT Accreditation trial on **26 October 2021** at HORIBA-MIRA Proving Ground, Watling Street, Nuneaton, Warwickshire, CV10 0TU under the supervision of TRL.

The above machine has been tested against the accreditation requirements as provided in "Accreditation and Quality Assurance of Dynamic Plate Test Survey Devices" document¹ dated September 2020.

This machine **has successfully met** the mandatory criteria. Some Network Authorities may also require specific level of performance in some or all of the additional tests. The performance of this machine in each test is summarised in the Annex to this test certificate.

This certificate supersedes any previous certificates issued by TRL.

Signed on behalf of TRL Limited

Patrick Werro

Valid From: Date of expiry: 26 October 2021 26 November 2022

¹ This document is available from TRL or from the UKRLG website (<u>https://www.ciht.org.uk/ukrlg-home/guidance/road-condition-information/data-collection/dynamic-plate-test-devices-dpt/</u>).



This report remains the property of TRL Limited and can be verified by emailing accreditation&qa@trl.co.uk TRL Limited Crowthorne House, Nine Mile Ride, Wokingham, RG40 3GA

Test Report 0127DPT/8002 214 Issue 13 Annex

The following parameters cover the configuration of the DPT device.

Component	Parameter
Load plate type	2-way segmented
Number of weights / buffers per side	4/2
Peak smoothing feature	Enabled

The following parameters must be passed to successfully meet the requirements of the trial.

Tested Parameter	Performance
Standard deviation of load corrected deflections	Pass
Mean Field Calibration Factor (FCF) for all sensors	Pass
Field Calibration Factor (FCF) for individual sensors	Pass
Mean Standard Deviation of the Deviation Ratio (SDDR) for all sensors	Pass
SDDR for individual sensors	Pass
Distance Travelled	Pass
Comments:	

The following parameters were also tested/reviewed. They are not currently mandatory requirements, however some Network Authorities may also require specific level of performance in some or all of these additional tests.

Tested Parameter	Performance level
OSGR coordinates (Easting and Northing)	Medium
Temperature at Depth	High
Surface temperature	Not Suitable
Air temperature	No Data Supplied

Comments:

3-dimensional location referencing data supplied as latitude and longitude. For this assessment the Auditor has completed the transformation to OSGRs. As such the contractor's coordinate transformation to OSGR has not been assessed.

Machine shows nonvariant values for surface temperatures in the survey data.

